

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number  
**WO 2004/000648 A1**

(51) International Patent Classification<sup>7</sup>: **B65B 1/06**, 1/28,  
37/02, G03G 15/08

(21) International Application Number:  
PCT/AU2003/000761

(22) International Filing Date: 20 June 2003 (20.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PS 3036 20 June 2002 (20.06.2002) AU

(71) Applicant and

(72) Inventor: **MEHAN, Terrence, John** [AU/AU]; 24 Ash  
Street, Soldiers Point, New South Wales 2317 (AU).

(74) Agent: **COWLE, Anthony, J**; Davies Collison Cave,  
Level 10, 10 Barrack Street, Sydney, New South Wales  
2000 (AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG,  
US, UZ, VC, VN, YU, ZA, ZM, ZW.







(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: DISPENSER DEVICE



(57) **Abstract:** The present invention relates generally to materials handling and in particular to apparatus for dispensing materials in fine powder form, such as for example toner. According to one aspect of the present invention, there is provided a dispenser device including: a dispenser device body (10) having an inlet end (14) and an outlet end (16); a transport passage (12) arranged therebetween, wherein the cross-sectional internal dimension at the inlet end (22) of the transport passage (12) are equal to or smaller than the cross-sectional internal dimension at the outlet end (16) of the transport passage (12); at least two sealable connector sections (18, 20), located at or near the inlet (14) and outlet ends (16), the device when in use being sealably connectable with filler vessels and unfilled vessels respectively. The arrangement is such that the sealable connection between said dispenser device and said unfilled vessel provides a substantially air tight seal so that air within the unfilled vessel is displaced by powder from the filler vessel and passes through the transport passage during the filling operation. This provides for a significant advantage in that the air causes agitation of the material within the passage, reducing the chances of clogging and blockage.